FORM PTO-1990 US DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEYS DOCKET NUMBER								
TRANSMERAL LETTER TO THE UNITED STATES	4278/PCT								
DESIGNATED/ELECTED OFFICE (DO/EO/US)	U.S. APPLICATION NO (If known see 37 CFR 1 5)								
CONCERNING A FILING UNDER 35 U.S.C. 371	(unknown to October 780 3								
INTERNATIONAL APPLICATION NO. INTERNATIONAL FILING DATE 22. September, 2000 (22.59.00	PRIORITY DATE CLAIMED 23.September 1999 (23.09.99)								
TITLE OF INVENTION Method and Device for Inserting Imple	ants Into Human Organs								
APPLICANT(S) FOR DOJEOJUS Oliver ROEHE; Horst LAUBE; Martin MATTHAEUS									
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the fo	llowing items and other information								
1. X This is a FIRST submission of items concerning a filing under 35 U.S.C. 371.									
2. This is a SECOND or SUBSEQUENT submission of items concerning a filing und	er 35 U.S.C. 371.								
3. X This express request to begin national examination procedures (35 U.S.C. 371(f) at examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) A proper Demand for International Preliminary Examination was made by the 19th	and PCT Articles 22 and 39(1).								
4 X A proper Demand for International Preliminary Examination was made by the 19th 5 X A copy of the International Application as filed (35 U.S.C. 371(c)(2))	month from the earnest claimed priority date.								
a. is transmitted herewith frequired only if not transmitted by the Int	ernational Bureau).								
b. 🕱 has been transmitted by the International Bureau.									
c. is not required, as the application was filed in the United States Re									
6. X A translation of the International Application into English (35 U.S.C. 371(· · · · ·								
a. \(\square \) are transmitted herewith (required only if not transmitted by the lift have been transmitted by the later rational Division.)	iternational Bureau).								
b. have been transmitted by the International Bureau.									
c. have not been made; however, the time limit for making such amendments has NOT expired.									
d. X have not been made and will not be made. A translation of the amondments to the plains and to DCT A sixty 10 (25 U.S.C. 2014,)(2))									
8 A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). 9 X An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).									
10. A translation of the annexes to the International Preliminary Examination (35 U.S.C. 371(c)(5)).	Report under PCT Article 36								
Items 11. to 16. below concern document(s) or information included:									
11. X An Information Disclosure Statement under 37 CFR 1.97 and 1.98, Form	PTO-1449. 2 references.								
12 An assignment document for recording. A separate cover sheet in compli									
13. X A FIRST preliminary amendment, to minimize the filing X A SECOND or SUBSEQUENT preliminary amendment.	166.								
A substitute specification.									
15. A change of power of attorney and/or address letter.	•								
16 X Other items or information:									
a. a return receipt postcard; e) marked- b. Form PTO-2038 (Credit Card Payment Form); c. 6 Figs. on 2 sheets of drawings; d. copy of International Search Report (and Engle	tup version of Spec. Pgs. 1-5,8.								
NOTE: The priority of German Patent Application 199 Federal Republic of Germany on September 23, 35 U.S.C. §119.	45 587.2, filed in the								
NOTE: This application has been assigned to: co.don of: Warthes	str. 21								
The Assignment is being submitted for records									
page 1 of 2 USP	S EXPRESS MAIL								

EV 059 670 853 US FEBRUARY 14 2002 FEBRUARY 14

(unknown Ut/o	Dela Signat	ATTORNEYS DOCKET NUMBER 4278/PCT						
	wing fees are submitte	CALCULATIONS	PTO USE ONLY					
	L FEE (37 CFR 1.492	Į						
Neither internal	tional preliminary exam	l						
		1.445(a)(2)) paid to USPTO repared by the EPO or JPO	XXXXXXXXX					
International pr	reliminary examination	fee (37 CFR 1.482) not paid to out prepared by the EPO or JPO	\$890.00					
		fee (37 CFR 1.482) not paid to USP 5(a)(2)) paid to USPTO	TO but					
		n fee paid to USPTO (37 CFR 1.482 ns of PCT Article 33(1)-(4)						
		n fee paid to USPTO (37 CFR 1.48) PCT Article 33(1)-(4)		·				
		OPRIATE BASIC FEE AM		\$ 890.00				
		path or declaration later than 20 date (37 CFR 1.492(e)).	30	s 0				
CLAIMS	NUMBER FILED	NUMBER EXTRA	` RATE					
Total claims	23 - 20	= 3	X \$18.00	\$ 54.00				
Independent claims	3 - 3		X \$78.00	s 0				
} - `~~`	NDENT CLAIM(S) (if a	pplicable)	+ \$260.00	S 0				
i.i.	TOTA	L OF ABOYE CALCULAT	TIONS =	\$ 944.00				
must also be filed	for filing by small entit (Note 37 CFR 1.9, 1.2	y, if applicable. A Small Entity State, 1.28).	tement	s 0				
i i		SUBT	TOTAL =	\$944.00				
	\$130.00 for furnishing carliest claimed priorit	s 0						
Ü		\$944.00						
		TOTAL NATION ent (37 CFR 1.21(h)). The assignment (37 CFR 3.28, 3.31). \$40.00 pe	ent must be	\$ 40.00				
- A	i eke Mae ada j	TOTAL FEES ENC	LOSED =	\$984.00				
		Amount to be:	s					
		refunded charged	S					
Form	PTO-2038 (Credit	Card Payment Form)			.1			
a. X XXXXXXX	15 IX in the amount of \$	Card Payment Form) to cover the abo	ve fees is enclos	sed.				
A dupl	charge my Deposit Accicate copy of this sheet	count No in the is enclosed.	amount of \$	to co	over the above fees.			
c. The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 50-0507 . жижирынских киру и Кинкульских инструменты в профессов на п								
		e limit under 37 CFR 1.494 or 1.4 ranted to restore the application		•	evive (37 CFR			
	Ü			. 1 01				
SEND ALL CORR		1/1/1/2 7	Jacob					
CUSTOMER	NO.: 021553	ATURE						
HCDC	EXPRESS MAI			er F. Fasse	2/14/02			
1		NAMI		-1.400				
	59 670 853	_	3613					
FEBRU	JARY 14 200	STRATION NUMBER						

DOCKET NO.: 4278/PCT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

IN THE MATTER OF THE PCT NATIONAL PHASE PATENT APPLICATION

OF: Oliver ROEHE et al.

USSN: TO BE ASSIGNED - NEW

FILED: February 14, 2002

FOR: Method and Device for Inserting

Implants Into Human Organs

INTERNATIONAL SERIAL NO.: PCT/DE00/03310

INTERNATIONAL FILING DATE: 22. September, 2000 (22.09.00)

ASSISTANT COMMISSIONER FOR PATENTS BOX PCT

WASHINGTON, D. C. 20231

February 14, 2002

FIRST PRELIMINARY AMENDMENT TO MINIMIZE THE FILING FEE

Dear Sir:

In order to minimize the filing fee, please amend the above identified patent application as follows before calculating the filing fee.

Referring to the Literal Translation of International Application $\underline{\text{PCT/DE00/03310}}$

In the Claims:

Claims ${\bf 1}$ and ${\bf 2}$ are maintained for calculating the filing fee. Please cancel claims ${\bf 3}$ to ${\bf 8}$.

REMARKS:

After calculating the filing fee, please further enter the accompanying Second Preliminary Amendment which introduces new claims 9 to 31 for examination.

Respectfully submitted,

Oliver ROEHE et al.

Applicant,

WFF:ar/4278/PCT Encls.: postcard

USPS EXPRESS MAIL EV 059 670 853 US

FEBRUARY 14 2002

Walter F. Passe Patent Attorney

Reg. No.: 36132

Tel. No.: (207) 862-4671 Fax. No.: (207) 862-4681

P. O. Box 726

Hampden, ME 04444-0726

DOCKET NO.: 4278/PCT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

IN THE MATTER OF THE PCT NATIONAL PHASE PATENT APPLICATION

OF: Oliver ROEHE et al.

USPS EXPRESS MAIL

USSN: TO BE ASSIGNED - NEW

EV 059 670 853 US

FILED: February 14, 2002

FEBRUARY 14 2002

FOR: Method and Device for Inserting

Implants Into Human Organs

INTERNATIONAL SERIAL NO.: PCT/DE00/03310

INTERNATIONAL FILING DATE: 22. SEPTEMBER, 2000 (22.09.00)

ASSISTANT COMMISSIONER FOR PATENTS

BOX PCT

WASHINGTON, D. C. 20231

February 14, 2002

SECOND PRELIMINARY AMENDMENT

Dear Sir:

After calculating the filing fee, but before the first examination, please amend the above identified application as follows.

Referring to the Literal Translation of International Application $\underline{\text{PCT/DE00/03310}}$

In the Specification:

Please delete and replace the heading at page 1, above line 1, to read as follows:

TITLE OF THE INVENTION

Please insert a new heading at page 1, following line 1 and above line 2, to read as follows:

FIELD OF THE INVENTION

Please insert a new heading at page 1, following line 5 and above line 6, to read as follows:

BACKGROUND INFORMATION

Please delete and replace the paragraph at page 1, lines 6 to 16, to read as follows:

In order to prevent, or at least reduce to a minimum, the immune reaction of the human organism with respect to implanted organ parts which are foreign to the body, and in order to prolong the long term durability or service life of special biological implants, it is an already known measure to coat the surfaces of the implants with living cells before the implantation into the human organism. Ideally, homologous cells, i.e. the body's own cells, or cells identical thereto, are concerned in this context. In that regard, the coating of the implants can be carried out in an especially advantageous manner in an apparatus as is described in the German Patent 198 34 396 C1 and corresponding U. S. Patent 6,214,407.

Please insert a heading at page 2, following line 6, and above line 7 to read as follows:

SUMMARY OF THE INVENTION

Please delete and replace the paragraph at page 3, lines 5 to 22, to read as follows:

Therewith the invention has the advantage, that the elements that are to be connected with one another cannot be loosened or released from one another in an automatic or self-acting manner, also in connection with a pulsating internal pressure, as it exists in connection with the heart. By means of elastic seal edges, a sufficient seal to the inside and to the outside is ensured simultaneously. On the other hand, a loosening or releasing of connection is also still possible after several years of installed use, as the case may be, with the aid of a specially fitted disassembly tool. Thereby it is possible to fabricate the adapter element as well as the receiver element of a sterilizable body-compatible synthetic material. Finally, the adapter element provided in the apparatus according to the invention has the advantage that it can, without problems, be coated with living cells, together with the organ part that is to be implanted, preferably a biological as well as artificial heart valve, in the apparatus described in the German Patent 198 34 396 C1 and the corresponding U. S. Patent 6,214,407.

Please insert a heading at page 3, following line 22 and above line 23, to read as follows:

BRIEF DESCRIPTION OF THE DRAWINGS

11

12

13

Please insert a heading at page 4, following line 11 and above line 12, to read as follows:

DETAILED DESCRIPTION OF A PREFERRED EXAMPLE EMBODIMENT OF THE INVENTION

In the Claims:

Please cancel Claims 1 and 2.

Claims 3 to 8 have previously been cancelled in applicants' First Preliminary Amendment.

Please enter new claims 9 to 31 as follows.

9. (new) A system for inserting an implant into a human organ comprising:

an adapter element comprising a ring-shaped adapter body and an annular adapter flange projecting from said adapter body; and

a receiver element comprising a ring-shaped receiver body and an annular receiver flange projecting from said receiver body;

wherein:

said adapter element is adapted to be connected to an implant, said receiver element is adapted to be connected to a human organ, and said adapter element and said receiver element are adapted to be connected to each other.

10. (new) The system according to claim 9, wherein said adapter flange is adapted to be connected to the implant, said receiver flange is adapted to be connected to the human organ, and said adapter body and said receiver body are adapted to be connected to each other.

- 1 11. (new) The system according to claim 10, wherein said receiver body has an external threading.
- 1 12. (new) The system according to claim 11, wherein said
 2 adapter body has an internal threading adapted to mate with
 3 said external threading of said receiver body.
 - 13. (new) The system according to claim 12, wherein said internal threading and said external threading are each respectively provided with mutually cooperating self-locking guide parts.
 - 14. (new) The system according to claim 12, wherein said receiver flange projects radially outwardly from said receiver body and said adapter flange projects radially inwardly from said adapter body.
- 1 15. (new) The system according to claim 10, wherein said 2 receiver flange projects radially outwardly from said 3 receiver body and said adapter flange projects radially 4 inwardly from said adapter body.
- 1 **16.** (new) The system according to claim 10, wherein said adapter body has an internal threading adapted to mate with said external threading of said receiver body.

- 1 17. (new) The system according to claim 10, wherein said
 2 adapter body and said receiver body are respectively
 3 provided with interengaging bayonet lock fastener
 4 components.
 - 18. (new) The system according to claim 10, wherein said adapter flange has first elements adapted to receive a suture to connect said adapter flange to the implant, and said receiver flange has second elements adapted to receive a suture to connect said receiver flange to the human organ.
 - 19. (new) The system according to claim 18, wherein said first elements are first throughholes in said adapter flange and said second elements are second throughholes in said receiver flange.
 - 20. (new) The system according to claim 10, further comprising said implant, a first suture connecting said adapter flange to said implant, and a second suture connecting said receiver flange to the human organ.
- 1 21. (new) The system according to clam 20, further comprising
 2 a coating layer of living cells covering a surface of said
 3 implant and a surface of said adapter element.
- 1 22. (new) The system according to claim 20, wherein said implant is a biological heart valve.

2

3

4

, 5

6 light bight bight 1 1 2

13 114 144

2

2

3

1

2

3

3

- 1 23. (new) The system according to claim 20, wherein said implant is an artificial heart valve.
- 1 24. (new) A system for inserting an implant into a human organ, comprising:

an implant;

an adapter element comprising a ring-shaped adapter body and an annular adapter flange projecting radially from said adapter body;

a first suture connecting said adapter flange to said implant;

a receiver element comprising a ring-shaped receiver body that is dimensioned and adapted to mate with and releasably connect with said adapter body, and an annular receiver flange that projects radially from said receiver body and is adapted to be connected to a human organ; and

a second suture adapted to connect said receiver flange to the human organ.

- 25. (new) The system according to claim 24, further comprising an integral coating layer of living cells continuously integrally covering a surface of said implant and an adjoining surface of said adapter element.
- 26. (new) The system according to claim 24, wherein said adapter body has a first threading, said receiver body has a second threading, and said first and second threadings

3

5

6

3

- are configured and adapted to be threadingly engaged with each other to releasably connect said receiver body with said adapter body.
- 1 27. (new) A method of inserting an implant into a human organ,
 2 comprising the steps:
 - a) providing an implant;
 - b) connecting said implant to an adapter element;
 - c) suturing a receiver element to a human organ; and
 - d) connecting said adapter element, with said implant connected thereto, to said receiver element.
 - 28. (new) The method according to claim 27, wherein said connecting of said adapter element to said receiver element comprises rotating said adapter element relative to said receiver element.
 - 29. (new) The method according to claim 28, wherein said receiver element and said adapter element respectively include first and second threadings, and said rotating of said adapter element relative to said receiver element comprises engaging and screwing together said first and second threadings.
- 1 30. (new) The method according to claim 28, wherein said
 2 receiver element and said adapter element respectively
 3 include bayonet lock fastener components, and said rotating

1

2

of said adapter element relative to said receiver element comprises engaging and locking together said bayonet lock fastener components.

31. (new) The method according to claim 27, further comprising an additional step, performed after said step b) and before said step d), of coating a surface of said adapter element and of said implant connected to said adapter element with a coating layer of living cells.

In the Abstract:

Please delete and replace the heading and paragraph at page 8, lines 1 to 17, to read as follows:

ABSTRACT OF THE DISCLOSURE

In a method for inserting an implant, such as a biological or artificial heart valve into a human organ, first the implant is provided with an adapter element, then a receiver element that is adapted to fit the adapter element is sutured to the recipient organ, and finally the adapter element is connected to the receiver element. The receiver element and the adapter element are each ring-shaped and are provided with matched interengageable threadings. They are connected with one another by relative rotation via a self-locking bayonet lock. Before being connected to the receiver element, the implant together with the adapter element are coated with living cells. Both the receiver

element and the adapter element respectively have flanges that include elements for being sutured together with the recipient organ or the implant.

REMARKS:

The original specification was a literal translation of the PCT International Application. The specification has now been amended for better conformance with typical U. S. format. All of the amendments are supported by the substance and the context of the original disclosure, and no new matter has been added. A marked-up version of the amended portions of the specification is enclosed. Please enter these amendments.

The literally translated PCT claims 1 to 8 have been replaced by new claims 9 to 31, which have been drafted "from the ground up" in consideration of typical U. S. form, style and practice. The new claims 9 to 31 are based on the features of the original claims and the original description, and do not include any new matter. Examination of the present U. S. National Phase Application is to proceed on the basis of the new claims 9 to 31.

3) Favorable consideration and allowance of claims 9 to 31 are respectfully requested.

Respectfully submitted,

Oliver ROEHE et al.

Applicant

WFF:ar/4278/PCT Encls.: postcard

USPS EXPRESS MAIL EV 059 670 853 US FEBRUARY 14 2002 Walter F. Fasse Patent Attorney

Reg. No.: 36132

Tel. No.: (207) 862-4671 Fax. No.: (207) 862-4681

P. O. Box 726

Hampden, ME 04444-0726

10/049703 JC11 Rec'd PCT/PTO 14 FEB 2002

Marked-up VERSION"

DOCKET NO: 4278/PCT

INVENTORS: Oliver ROEHE

Horst LAUBE

Martin MATTHAEUS

LITERAL TRANSLATION OF PCT INTERNATIONAL APPLICATION PCT/DE00/03310 AS FILED ON SEPTEMBER 22, 2000

TITLE OF THE IN VENTION

Method and Device for Inserting Implants Into Human Organs

FIELD OF THE INVENTION

The invention relates to a method for the insertion of implants into human organs, especially for the installation of biological as well as artificial heart valves, as well as an apparatus for carrying out a method of this kind.

BACKGROUND IN FORMATION

In order to prevent, or at least reduce to a minimum, the immune reaction of the human organism with respect to implanted organ parts which are foreign to the body, and in order to prolong the long term durability or service life of special biological implants, it is an already known measure to coat the surfaces of the implants with living cells before the implantation into the human organism. Ideally, homologous cells, i.e. the body's own cells, or cells identical thereto, are concerned in this context. In that regard, the coating of the implants can be carried out in an especially advantageous manner in an apparatus as is described in the German Patent 198 34 396 CI:] and corverpointing U.S. Patent 6,214,407,

In any event, it is important in this procedure, that the vital cell layer of the thusly prepared organ parts, which are especially biological as well as synthetic or artificial heart

4278/PCT/WFF:ar

_ USPS EXPRESS MAIL
EV 059 670 853 US
FEBRUARY 14 2002

\ \ ./

25

valves, is not destroyed by the surgical implantation technique, or are implanted into the human body, in this case into the recipient heart, in the shortest possible operation time after the completed coating, so that the applied cells do not already begin to die off before the successful completion of the transplantation.

SUMMARY OF THE INVENTION

An object of the invention is to develop a method of the above initially described type in such a manner so that it is ensured that artificial or biological organ parts, especially those that have been subjected to a cell coating before the implantation, can be inserted into the recipient organ in a short time and in an irritation-free manner to the extent possible. Moreover, it is an object of the invention, to provide an apparatus for carrying out a method of this type.

The invention achieves the first object by a method in which the implant is provided with an adapter element, a receiver element adapted or matched to the adapter element is sutured together with the recipient organ, and the adapter element is connected with the receiver element. The further object is achieved according to the invention by an apparatus, in which both the receiver element as well as the adapter element are embodied with a ring shape and are respectively provided with a flange-like shoulder or projection.

In an advantageous further development of the invention, it is provided in this context, that the connection of adapter element

and receiver element is achieved via a fastener, that is embodied as a bayonet lock and essentially only requires a rotation or turning. Moreover, this fastener is equipped with self-locking guide elements in an advantageous embodiment of the invention.

Therewith the invention has the advantage, that the elements that are to be connected with one another cannot be loosened or released from one another in an automatic or self-acting manner, also in connection with a pulsating internal pressure, as it exists in connection with the heart. By means of elastic seal edges, a sufficient seal to the inside and to the outside is ensured simultaneously. On the other hand, a loosening or releasing of the connection is also still possible after several years of installed use, as the case may be, with the aid of a specially fitted disassembly tool. Thereby it is possible to fabricate the adapter element as well as the receiver element of a sterilizable body-compatible synthetic material. Finally, the adapter element provided in the apparatus according to the invention has the advantage that it can, without problems, be coated with living cells, together with the organ part that is to be implanted, preferably a biological as well as artificial heart valve, in the apparatus described in the German Patent 198 34 396 CIET and the corresponding U.S. Patent 6, 214, 407.

BRIEF DESCRIPTION OF THE DRAWINGS

In the following, the invention shall be described in further detail in connection with an example embodiment illustrated as a general principle in the drawing. Therein:

20

- Fig. 1 shows a top plan view onto a receiver element,
- Fig. 2 shows the element according to Fig. 1 in a partially sectioned side illustration,
- Fig. 3 shows an enlarged detail illustration III of the arrangement according to Fig. 2,
- Fig. 4 shows a partially sectioned side illustration of an adapter element,
- Fig. 5 shows an enlarged detail illustration V of the arrangement according to Fig. 4, and
- Fig. 6 shows an enlarged detail illustration of the threading in the screwed-together position.

DESCRIPTION OF A PREFERED EXAMPLE EMBOUMENT THE INVENTION

The receiver element 1 illustrated in the Figures 1 to 3 essentially consists of a ring that is provided with a flange-like shoulder or projection 2 and that has a threading 3 on its outer surface. In the presently illustrated example embodiment, in which the receiver element 1 serves for the implantation of an artificial heart valve, this ring, with an outer diameter of 29 mm and a width of about 3 mm, comprises a four-fold sharp V-thread with a pitch of 8 mm and a web width of 1 mm. In the presently illustrated example embodiment, the web height amounts to 0.5 mm. The flange 2 is provided with a set of bored through holes 4, which comprise a diameter of 0.4 mm in the presently

illustrated example embodiment, and which serve for the suturing with the recipient organ, in this case the recipient heart.

The adapter element 5 illustrated in the Figures 4 and 5 is similarly embodied as a ring with a flange-like shoulder or projection 6, whereby the flange is again provided with bored holes 7. In its interior, the adapter element 5 is provided with an internal threading 8, of which the dimensions are adapted or matched to the external threading of the receiver element 1. Both elements 1 and 5 consist of a sterilizable body-compatible synthetic or plastic.

In connection with the insertion of an artificial heart valve, before the actual operation, this valve is first connected with the adapter element 5, in this case being sutured together, and together with the adapter element is coated on the surface with living cells in an apparatus especially embodied for this purpose. Then, for beginning the transplantation operation, first the receiver element 1 is sutured into the heart, and in the following step the coated combination of heart valve and adapter element 5 is inserted into the receiver element 1, and both components are mechanically securely connected with one another by relative rotation or turning by about 30 angular degrees.

15

ABSTRACT OF THE DISCLOSURE

, such as a biological or ortificial heart val.

In a method for the insertion of implants into human organs, especially for the implantation of biological as well as artificial heart valves, first the implant is provided with an adapter element, then a receiver element that is matched or the adapter element is sutured to the recipient organ, and finally the adapter element is connected with the receiver element. Receiver element and adapter element are embodied with a ring matched interengageable shape, and are provided with threadings [that are matched to one another. They are connected with one another by turning or7 rotation via a self-locking bayonet lock.

being connected to Before the connection with the receiver element, the implant together with the adapter element are coated with living cells. Both the receiver element [as well as] the adapter element [are] respectively [provided with] $ot \pm 1$ ange-like projections which, on their part, comprise construcflanges flut include tive elements for suturing together with the recipient organ or being sutured the implant.

10/049703 JC11 Head POTAPIO 14 FEB 2002

15

DOCKET NO: 4278/PCT

INVENTORS: Öliver ROEHE

Horst LAUBE

Martin MATTHAEUS

LITERAL TRANSLATION OF PCT INTERNATIONAL APPLICATION PCT/DE00/03310 AS FILED ON SEPTEMBER 22, 2000

Method and Device for Inserting Implants Into Human Organs

The invention relates to a method for the insertion of implants into human organs, especially for the installation of biological as well as artificial heart valves, as well as an apparatus for carrying out a method of this kind.

In order to prevent, or at least reduce to a minimum, the immune reaction of the human organism with respect to implanted organ parts which are foreign to the body, and in order to prolong the long term durability or service life of special biological implants, it is an already known measure to coat the surfaces of the implants with living cells before the implantation into the human organism. Ideally, homologous cells, i.e. the body's own cells, or cells identical thereto, are concerned in this context. In that regard, the coating of the implants can be carried out in an especially advantageous manner in an apparatus as is described in the German Patent 198 34 396 C1.

In any event, it is important in this procedure, that the vital cell layer of the thusly prepared organ parts, which are especially biological as well as synthetic or artificial heart

-1-

USPS EXPRESS MAIL EV 059 670 853 US FFBRUARY 14 2002

25

5

valves, is not destroyed by the surgical implantation technique, or are implanted into the human body, in this case into the recipient heart, in the shortest possible operation time after the completed coating, so that the applied cells do not already begin to die off before the successful completion of the transplantation.

An object of the invention is to develop a method of the above initially described type in such a manner so that it is ensured that artificial or biological organ parts, especially those that have been subjected to a cell coating before the implantation, can be inserted into the recipient organ in a short time and in an irritation-free manner to the extent possible. Moreover, it is an object of the invention, to provide an apparatus for carrying out a method of this type.

The invention achieves the first object by a method in which the implant is provided with an adapter element, a receiver element adapted or matched to the adapter element is sutured together with the recipient organ, and the adapter element is connected with the receiver element. The further object is achieved according to the invention by an apparatus, in which both the receiver element as well as the adapter element are embodied with a ring shape and are respectively provided with a flange-like shoulder or projection.

In an advantageous further development of the invention, it is provided in this context, that the connection of adapter element

25

5

and receiver element is achieved via a fastener, that is embodied as a bayonet lock and essentially only requires a rotation or turning. Moreover, this fastener is equipped with self-locking guide elements in an advantageous embodiment of the invention.

Therewith the invention has the advantage, that the elements that are to be connected with one another cannot be loosened or released from one another in an automatic or self-acting manner, also in connection with a pulsating internal pressure, as it exists in connection with the heart. By means of elastic seal edges, a sufficient seal to the inside and to the outside is ensured simultaneously. On the other hand, a loosening or releasing of the connection is also still possible after several years of installed use, as the case may be, with the aid of a specially fitted disassembly tool. Thereby it is possible to fabricate the adapter element as well as the receiver element of a sterilizable body-compatible synthetic material. Finally, the adapter element provided in the apparatus according to the invention has the advantage that it can, without problems, be coated with living cells, together with the organ part that is to be implanted, preferably a biological as well as artificial heart valve, in the apparatus described in the German Patent 198 34 396 C1.

In the following, the invention shall be described in further detail in connection with an example embodiment illustrated as a general principle in the drawing. Therein:

20

5

- Fig. 1 shows a top plan view onto a receiver element,
- Fig. 2 shows the element according to Fig. 1 in a partially sectioned side illustration,
- Fig. 3 shows an enlarged detail illustration III of the arrangement according to Fig. 2,
- Fig. 4 shows a partially sectioned side illustration of an adapter element,
- Fig. 5 shows an enlarged detail illustration V of the arrangement according to Fig. 4, and
- Fig. 6 shows an enlarged detail illustration of the threading in the screwed-together position.

The receiver element 1 illustrated in the Figures 1 to 3 essentially consists of a ring that is provided with a flange-like shoulder or projection 2 and that has a threading 3 on its outer surface. In the presently illustrated example embodiment, in which the receiver element 1 serves for the implantation of an artificial heart valve, this ring, with an outer diameter of 29 mm and a width of about 3 mm, comprises a four-fold sharp V-thread with a pitch of 8 mm and a web width of 1 mm. In the presently illustrated example embodiment, the web height amounts to 0.5 mm. The flange 2 is provided with a set of bored through holes 4, which comprise a diameter of 0.4 mm in the presently

5

illustrated example embodiment, and which serve for the suturing with the recipient organ, in this case the recipient heart.

The adapter element 5 illustrated in the Figures 4 and 5 is similarly embodied as a ring with a flange-like shoulder or projection 6, whereby the flange is again provided with bored holes 7. In its interior, the adapter element 5 is provided with an internal threading 8, of which the dimensions are adapted or matched to the external threading of the receiver element 1. Both elements 1 and 5 consist of a sterilizable body-compatible synthetic or plastic.

In connection with the insertion of an artificial heart valve, before the actual operation, this valve is first connected with the adapter element 5, in this case being sutured together, and together with the adapter element is coated on the surface with living cells in an apparatus especially embodied for this purpose. Then, for beginning the transplantation operation, first the receiver element 1 is sutured into the heart, and in the following step the coated combination of heart valve and adapter element 5 is inserted into the receiver element 1, and both components are mechanically securely connected with one another by relative rotation or turning by about 30 angular degrees.


-5-


2

- 1. Method for the insertion of implants in human organs, especially for the installation of biological as well as artificial heart valves, characterized in that the implant is provided with an adapter element (5), a receiver element (1) adapted to the adapter element (5) is sutured together with the recipient organ, and the adapter element (5) is connected with the receiver element (1).
 - 2. Method according to claim 1, characterized in that the receiver element (1) and the adapter element (5) are provided with threadings (3, 8) adapted to each other, and are connected with each other by rotation, by means of a self-locking bayonet lock.
 - 3. Method according to claim 1 or 2, characterized in that the implant together with the adapter element (5) is coated with living cells before the connecting with the receiver element (1).
- Apparatus for carrying out the method according to one of the claims 1 to 3, characterized in that both the receiver element (1) as well as the adapter element (5) are embodied with a ring shape and are respectively provided with a flange-like projection (2, 6).

- 5. Apparatus according to claim 4, characterized in that the receiver element (1) is provided with an external threading (3).
- 1 **6.** Apparatus according to claim 4 or 5, characterized in that
 2 the adapter element (5) is provided with an internal
 3 threading (8).
 - 7. Apparatus according to one of the claims 5 or 6, characterized in that the threadings (3, 8) of both the receiver element (1) as well as the adapter element (5) are provided with self-locking guide parts.
 - 8. Apparatus according to one of the claims 4 to 7, characterized in that the flanges (2, 6) are provided with elements (4, 6) for suturing together with the recipient organ and the implant.

In a method for the insertion of implants into human organs, especially for the implantation of biological as well as artificial heart valves, first the implant is provided with an adapter element, then a receiver element that is matched or adapted to the adapter element is sutured to the recipient organ, and finally the adapter element is connected with the receiver element. Receiver element and adapter element are embodied with a ring shape and are provided with threadings that are matched to one They are connected with one another by turning or another. rotation via a self-locking bayonet lock. Before the connection with the receiver element, the implant together with the adapter element are coated with living cells. Both the receiver element as well as the adapter element are respectively provided with flange-like projections which, on their part, comprise constructive elements for suturing together with the recipient organ or the implant.








Fig.5




Fig.6

our Case No.: 4278

i deserting a piece aight (*) (i)	side this box			070:00:00						
Under the Paperwork Reduction Act of	1995, no persons are requ	U.S. Paten ired to respond to a collectio		PTO/SB/01 (10-00 for use through 10/31/2002, OMB 0651-003 Office: U.S. DEPARTMENT OF COMMERC nless it contains a valid OMB control numbe						
DECLARATION FO		Attorney Dec		4278						
DESIG		First Named	Inventor	Oliver ROEHE						
PATENT APP	LICATION		COMPLETE IF KNOWN							
(37 CFR		Application No	Application Number							
	WER OF ATTORNEY Declaration Filing Date									
Submitted OR with Initial	Submitted after In Filing (surcharge	itial Group Art Unit	ł .							
Filing	(37 ČFR 1.16 (e)) required)	Examiner Nan	ne							
er e										
As a below named inventor, I h	-									
My residence, mailing address, a		- '								
As a below named inventor, the My residence, mailing address, at believe I am the original, first are names are listed below) of the summer METHOD AND DEVICE.	id sole inventor (if only object matter which is cla	one name is listed below) or an original, t	first and joint inventor (if plural						
METHOD AND DEVI										
l l				ondrivo						
the specification of which	(Title of the Invention)								
is attached hereto OR was filed on (MM/DD/YYYY										
OR	00/22/2000									
	<u> </u>	as United S	tates Application	Number or PCT International						
Application Number PCT/DE0		amended on (MM/DD/YY		(if applicable).						
I hereby state that I have reviews amended by any amendment spe	ed and understand the o ecifically referred to abo	contents of the above ide. ve.	ntified specificat	ion, including the claims, as						
l acknowledge the duty to disclos in-part applications, material infor PCT international filing date of the	e information which is r mation which became a e continuation-in-part ap	naterial to patentability a available between the filin oplication.	s defined in 37 (ng date of the pr	CFR 1.56, including for continuation- for application and the national or						
I hereby claim foreign priority be	nefits under 35 U.S.C.	119(a)-(d) or 365(b) of a	ny foreign applic	cation(s) for patent or inventor's						
certificate, or 365(a) of any PCT Numerica, listed below and have certificate, or any PCT internation	also identified below	n which designated at lead by checking the hox a	ast one country any foreign, and	other than the United States of						
Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached? YES NO						
199 45 587.2	Fed. Rep. of Germany	09/23/1999		0000						
Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/028 attached hereto:										
I hereby claim the benefit under				أأكالا وبرونين فيناور فالتاكنات فالتناف والمتالي والمتالية						
Application Number(s)		e (MM/DD/YYYY)								
			Additional provisional application numbers are listed on a							
				nental priority data sheet B/02B attached hereto.						
<u> </u>										

USPS EXPRESS MAIL EV 059 670 853 US FEBRUARY 14 2002

ATTORNEY DOCKET NO. 4278

PTO/SB/01 (10-00)

Approved for use through 10/31/2002. OMB 0651-0032

U.S. Palent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 o United States of America, listed below and, inso United States or PCT International application in information which is material to patentability as and the national or PCT international filing date o	ofar as the subject the manner provided in 37 CFF	of matter of ded by the	of each of the first paragra	e claims of ph of 35 U	this application S.C. 112, I ack	n is not dis inowledge t	closed in the pri	or se
U.S. Parent Application or P Number	Parent Filing Date (MM/DD/YYYY)		e Pare	ent Pater (if appli				
Additional U.S. or PCT international applicat								
As a named inventor, I hereby appoint the following and Trademark Office connected therewith:	ng registered prac Customer Numbe		to prosecute	this applica	etion and to tran	Place	siness in the Pate Customer er Bar Code] 1 10 11 10 12 13 14 14 14 14 14 14 14
	tomer Number ar Code Label	021	553				bel here	021553 PATENT NO TRADEMARK OFF
I hereby declare that all statements ma are believed to be true; and further that made are punishable by fine or imprison validity of the application or any patent	at these staten nment, or both	nents wi 1. under	ere made v	vith the k	nowledge tha	at willful t	alse statemer	nts and the like so
NAME OF SOLE OR FIRST IN	ENTOR:			A peti	ion has be	en filed	for this un	signed inventor
Given Name <u>01iver</u>				Family or Sur		ЕНЕ		
Inventor's An Hote						5	th Febr Date	uary, 2002
Residence: City 27721 <u>Ritter</u>	Residence: City 27721 Ritterhude State Fed. Rep. of Country German Citizenship German							
Mailing Address c/o CO.DON	AG, Warth	estr.	21		····			
Mailing Address								
City Teltow	State			ZIP	14513		Fed. Rep Country G	
NAME OF SECOND INVENTOR	₹:			A peti	tion has be	een filed	for this un	signed inventor
Given Name <u>Horst</u> (first and middle [if any])				Family or Sur	Name name	LAUBE		
Inventor's Coluba							Date	ruary, 2002
Residence: City 10115 Berlin			State		1	kep. of German	yCitizenship	German
Mailing Address c/o CO.DO	N AG, War	thest	r. 21	···				
Mailing Address				T				
City Teltow	State			ZIP 1	4513		Fed. Rep Country G	. of ermany
Additional inventors are being name	ed on the 3	supplen	nental Addit	ional Inve	entor(s) shee	t(s) PTO/	SB/02A attacl	ned hereto.
HSPS EXPRESS MA					ATTO	DNEV	DOCKET	NO 4278

EV 059 670 853 US PAGE 2 OF $\frac{3}{}$ FEBRUARY 14 2002

											-
o teas	type	3	pius	npie	(+)	inside	this	pox	>	1+	
				- 3	٠,				_	, ,	

PTO/SB/02A (10-00)

Approved for use through 10/31/2002. OMB (651-0032

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION

ADDITIONAL INVENTOR(S) Supplemental Sheet Page 3 of 3

Name of Additional Joint Inventor, if an	y:		A petition has been	filed for t	his unsigned inventor	
Given <u>Martin</u> Name			Family Name MATT or Surname	HAEUS		
Inventor's Signature Uniting Ularton				5	th February, 2002	
Residence: City 14052 Berlin Dex State			Fed. Rep. of Country Germany		CitizenshipGerman	
Mailing Address c/o CO.DON AG, Warthe	str	. 21				
Mailing Address						
City Teltow	Sta	te	ZIP 14513	Count	Fed. Rep. of y Germany	
Name of Additional Joint Inventor, if any	/ :		A petition has been fil	ed for thi	s unsigned inventor	
Given Name	Family Name or Surname					
Inventor's Signature					Date	
Residence: City State			Country	· · · · · · · · · · · · · · · · · · ·	Citizenship	
Mailing Address						
Mailing Address				,		
City	ite	ZIP Country				
Name of Additional Joint Inventor, if any	/ :		A petition has been file	d for this	unsigned inventor	
Given Name			nmily Name Surname			
Inventor's Signature	· · · · · · · · · · · · · · · · · · ·				Date	
Residence: City	e	Country Citizenship				
Mailing Address			· · · · · · · · · · · · · · · · · · ·			
Mailing Address		·				
City	State	9	ZIP	Co	untry	

USPS EXPRESS MAIL EV 059 670 853 US ATTORNEY DOCKET NO. 4278

PAGE 3 OF 3

FEBRUARY 14 2002